# TECHNICAL DATA SHEET

Date of Issue: 2018/02/20

# Lithium Nitrate, technical grade

CAS-No. 7790-69-4

EC-No. 232-218-9

REACH No. 01-2119968667-16

Molecular Formula LiNO<sub>3</sub>

Product Number 401143

APPLICATION - strong oxidizing agent

- corrosion inhibitor, e.g. in absorption coolers

- additive in fire works

#### **SPECIFICATION**

LiNO3	min. 98.5 %	
H2O (200°C)	max. 0.5%	

## PHYSICAL PROPERTIES

Appearance Crystalline powder

Color colorless

Melting point/ range ca. 255 °C at 1,013 hPa (Information taken from reference works and the

literature.)

Flash point (Not applicable)

Decomposition temperature

from 450 °C

Density ca. 2.37 g/cm3 at 20 °C

Bulk density ca. 1,130 kg/m3

Water solubility 1,020 g/L at 20 °C

560 g/L at 30 °C

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.



Product Number: 401143 Date of Issue: 2018/02/20

Molecular weight 68.95 g/mol

Thermal Stability onset of decomposition: 450 °C

Additional Physical

**Properties** 

Solution enthalpy: + 300 cal (18 °C)

#### HANDLING & STORAGE

Handling Pay attention to the official safety regulations.

Storage Store under dry conditions. Product ist hygroscopic, tends to time consolidation and

forms agglomerates under prolonged storage.

#### TRANSPORT & PACKAGING

## UN number 2722

ADR	Class: 5.1	PG: III	Label: 5.1
RID	Class: 5.1	PG: III	Label: 5.1
IMDG	Class: 5.1	PG: III	Label: 5.1
IATA_C	Class: 5.1	PG: III	Packing instruction (cargo aircraft): 563
IATA_P	Class: 5.1	PG: III	Packing instruction (passenger aircraft): 559

# Hazard pictograms





Signal Word Warning

H&P Phrases See Safety Data Sheet

Labelling The labelling is according to EU-GHS classification ((EG) 1272/2008) and may vary

in other countries. Please refer to the respective Safety Data Sheet for your country.

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.



Product Number: 401143 Date of Issue: 2018/02/20

## Packaging

50kg polyethylene bag in fibre drum or 4 x 25kg polyethylene bags in 100kg fibre drum.

## OTHER INFORMATION

Further Related Documents

Safety Data Sheet

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Albemarle Corporation and its subsidiaries and affiliates. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.

